

<b>Material Safety Data Sheet</b> <b>Issue Date: 01-11-02</b>		<b>Product Code:</b> <b>VT-210 High Performance Sealant</b>
--	---	--

## 1. Identification of the substance/preparation and of the company/undertaking

**Product name:** VT-210 High Performance Sealant

**Company:** Vital Technical Sdn. Bhd.  
No.7, Jalan Helang Hindik (Jalan 117)  
Kepong Baru Industrial Estate  
52100 Kuala Lumpur, Malaysia

Tel: +603-62734088  
Fax: +603-62736685  
Email: sales@vitaltechnical.com  
Website: www.vitaltechnical.com

## 2. Composition/information on ingredients

Mixture of polydimethylsiloxanediol and polydimethylsiloxane with fillers, pigments and a cross linking agent.

Hazardous component:

Component	CAS No.	Wt%	Exposure Limits
Silica, Amorphous	007631869	11	OSHA PEL: TWA 15mg/m <sup>3</sup> total dust, 5mg/m <sup>3</sup> respirable fraction. ACGIH TLV: TWA 10mg/m <sup>3</sup> respirable particulate
Methyl tri (ethylemethylketoxime silane)	22984549	6	See ethyl methylketoxime comments
Chromic Oxide	001308389	4	OSHA PEL and ACGIH TLV, as chromium: TWA 0.5mg/m <sup>3</sup>
Iron Oxide	001309371	4	OSHA PEL (final rule) (fume):TWA 10mg/m <sup>3</sup> ACGIH TLV (fume), as iron: TWA 5mg/m <sup>3</sup>
Black Iron Oxide	001317619	4	Observe iron oxide limits (fume): TWA 10mg/m <sup>3</sup> . ACGIH TLV (fume), as iron: TWA 5mg/m <sup>3</sup>
Titanium Dioxide	013463677	4	OSHA PEL (final rule): TWA 10mg/m <sup>3</sup> total dust. ACGIH TLV: TWA 10mg/m <sup>3</sup>
C.I Pigment Blue 29	057455375	4	Observe particulate limits. OSHA dust, 5mg/m <sup>3</sup> respirable fraction. ACGIH TLV: TWA 10mg/m <sup>3</sup> inhalable particulate, 3mg/m <sup>3</sup> respirable particulate
Yellow Iron Oxide	051274001	3	OSHA (final rule) (fume): TWA 10mg/m <sup>3</sup> . ACGIH TLV (fume), as iron: TWA 5g/m <sup>3</sup> .
Antimony Chromium Manganese Titanium Brown Rutile	069991680	3	Observe Final rules. Chromium Oxide: (OSHA PEL and ACGIH TLV, as chrome: TWA 0.5m <sup>3</sup> ), Antimony Oxide (OSHA PEL and ACGIH TLV, as antimony: 0.5mg/m <sup>3</sup> ) Manganese Oxide: (OSHA PEL), as manganese: Ceiling 5mg/m <sup>3</sup> ; ACGIH TLV: TWA 5g/m <sup>3</sup>
Aminoethyl Aminopropyl Trimethoxysilane	001760243	2	See methyl alcohol comments
Di(ethylmethyl ketoxime) methoxymeethyl silane	083817725	2	See enthyl methyl ketoxime and methyl alcohol components

<b>Material Safety Data Sheet</b> <b>Issue Date: 01-11-02</b>		<b>Product Code:</b> <b>VT-210 High Performance Sealant</b>
--	---	--

Aluminum	007429905	1	OSHA PEL (final rule): TWA 15mg/m <sup>3</sup> total dust, 5mg/m <sup>3</sup> respirable fraction. A ACGIH TLV (metal dust): TWA 10mg/m <sup>3</sup>
----------	-----------	---	--

Further information:  
This sheet only contains safety relevant data. For specific data, see Technical Data Sheet.

**3. Hazards identification**

May cause sensitization by skin contact

**4. First-aid measures**

- Take off immediately all contaminated clothing
- After skin contact: Clear with water and skin cleanser immediately
- After eye contact: Rinse with plenty of water immediately, seek medical advice if necessary
- After ingestion: Seek medical advice immediately

**5. Fire-fighting measures**

- Suitable extinguishing media: Water spray, foam, CO<sub>2</sub>, dry powder
- Unsuitable extinguishing media: -

**6. Accidental release measure**

- Methods for cleaning up: Take up mechanically

**7. Handling and storage**

- Handling: Ensure good ventilation during processing
- Protection against fire/explosion: General rules of fire prevention should be observed
- Storage: Keep container tightly closed and dry. Store in a well-ventilated area

**8. Exposure controls/personal protection**

- Ingredients with limiting values to be controlled  
TLV (TRGS 900/D): Not indicated
- Industrial hygiene: Remove immediately all contaminated clothing. Do not inhale vapours/aerosols
- Hand protection: Suitable protective gloves
- Eye protection: Protective goggles

<b>Material Safety Data Sheet</b> <b>Issue Date: 01-11-02</b>		<b>Product Code:</b> <b>VT-210 High Performance Sealant</b>
--	---	--

**9. Physical and chemical properties**

- Form: Pastry
- Color: Color varies
- Odour: Characteristic
- Melting temperature: Not applicable
- Boiling temperature (hPa): Not applicable
- Flash point: >320°C
- Ignition temperature: Not determined
- Vapour pressure (20°C): 15hPa
- Density (20°C): 1.03
- Solubility in water (20°C): Practically insoluble
- pH Value (g/l water) (°C): Not determined

**10. Stability and reactivity**

- Hazardous decomposition products: Z-butanone oxime through action of atmospheric humidity
- Hazardous reaction: No dangerous reaction known

**11. Toxicological information**

- Skin: May cause sensitization \* (Methyl tri (enthylmethylketoxime))
- reaction
- Eyes: Possibility irritating
- Further information: \* The data are derived from the labeling according to the EC Dangerous Preparation Directive

**12. Ecological information**

No data available (preparation)

**13. Disposal considerations**

Can be land-filled for cured product or burned in a chemical incinerator equipped with an afterburner and scrubber. Do not dispose the emptied container unlawfully. Observed all federal, state and local laws.

**14. Transport information**

No dangerous goods under the transport regulations

<b>Material Safety Data Sheet Issue Date: 01-11-02</b>		<b>Product Code: VT-210 High Performance Sealant</b>
--	---	--

**15. Regulatory information**

- Labeling (EC): According to the Dangerous Perparation Directive (88/379/EEC) contains:
  - Butan-Z-One O, O', O" – (methyliylidne) trioxime
  - Hazard symbol: Xi = Irritant
  - R-pharases 43: May causes sensitization by skin contact
  - S-pharases: Z = Keep out of reach of children
  - 24/25 = Avoid contact with skin and eyes
  - 37 = Wear suitable gloves
  - 46 = If swallowed, seek medical advice immediately and show this container or label

**16. Other information**

The details contained herein are based on our present state of knowledge and experience are characterize our product with regard to any possible safety requirement. We do, however, pass them on without any warranty or property assurances.