

Material Safety Data Sheet Issue Date: 01-11-02		Product Code: VT-211 Weatherproofing Sealant
--	---	---

1. Identification of the substance/preparation and of the company/undertaking

Product name: VT-211 Weatherproofing Sealant

Company: Vital Technical Sdn. Bhd.
No.7, Jalan Helang Hindik (Jalan 117)
Kepong Baru Industrial Estate
52100 Kuala Lumpur, Malaysia

Tel: +603-62734088
Fax: +603-62736685
Email: sales@vitaltechnical.com
Website: www.vitaltechnical.com

2. Composition/information on ingredients

Mixture of polydimethylsiloxanediol and polydimethylsiloxane with fillers, pigments and a cross linking agent.

Hazardous component:

Component	CAS No.	Wt%	Exposure Limits
Silica, Amorphous	007631869	11	OSHA PEL: TWA 15mg/m ³ total dust, 5mg/m ³ respirable fraction. ACGIH TLV: TWA 10mg/m ³ inhalable particulate, 3mg/m ³ respirable particulate
Methyl tri (ethylemethylketoxime silane)	22984549	6	See ethyl methylketoxime comments
Chromic Oxide	001308389	4	OSHA PEL and ACGIH TLV, as chromium: TWA 0.5mg/m ³
Iron Oxide	001309371	4	OSHA PEL (final rule) (fume):TWA 10mg/m ³ ACGIH TLV (fume), as iron: TWA 5mg/m ³
Black Iron Oxide	001317619	4	Observe iron oxide limits (fume): TWA 10mg/m ³ . ACGIH TLV (fume), as iron: TWA 5mg/m ³
Titanium Dioxide	013463677	4	OSHA PEL (final rule): TWA 10mg/m ³ total dust. ACGIH TLV: TWA 10mg/m ³
C.I Pigment Blue 29	057455375	4	Observe particulate limits. OSHA dust, 5mg/m ³ respirable fraction. ACGIH TLV: TWA 10mg/m ³ inhalable particulate, 3mg/m ³ respirable particulate
Yellow Iron Oxide	051274001	3	OSHA (final rule) (fume): TWA 10mg/m ³ . ACGIH TLV (fume), as iron: TWA 5g/m ³ .
Antimony Chromium Manganese Titanium Brown Rutile	069991680	3	Observe Final rules. Chromium Oxide: (OSHA PEL and ACGIH TLV, as chrome: TWA 0.5m ³), Antimony Oxide (OSHA PEL and ACGIH TLV, as antimony: 0.5mg/m ³) Manganese Oxide: (OSHA PEL), as manganese: Ceiling 5mg/m ³ ; ACGIH TLV: TWA 5g/m ³
Aminoethyl Aminopropyl Trimethoxysilane	001760243	2	See methyl alcohol comments

Material Safety Data Sheet Issue Date: 01-11-02		Product Code: VT-211 Weatherproofing Sealant
--	---	---

Di(ethylmethyl ketoxime) methoxymeethyl silane	083817725	2	See ethyl methyl ketoxime and methyl alcohol components
Aluminum	007429905	1	OSHA PEL (final rule): TWA 15mg/m ³ total dust, 5mg/m ³ respirable fraction. A ACGIH TLV (metal dust): TWA 10mg/m ³

Further information:
This sheet only contains safety relevant data. For specific data, see Technical Data Sheet.

3. Hazards identification

May cause sensitization by skin contact

4. First-aid measures

- Take off immediately all contaminated clothing
- After skin contact: Clear with water and skin cleanser immediately
- After eye contact: Rinse with plenty of water immediately, seek medical advice if necessary
- After ingestion: Seek medical advice immediately

5. Fire-fighting measures

- Suitable extinguishing media: Water spray, foam, CO₂, dry powder
- Unsuitable extinguishing media: -

6. Accidental release measure

- Methods for cleaning up: Take up mechanically

7. Handling and storage

- Handling: Ensure good ventilation during processing
- Protection against fire/explosion: General rules of fire prevention should be observed
- Storage: Keep container tightly closed and dry. Store in a well-ventilated area

8. Exposure controls/personal protection

- Ingredients with limiting values to be controlled TLV (TRGS 900/D): Not indicated
- Industrial hygiene: Remove immediately all contaminated clothing. Do not inhale vapours/aerosols
- Hand protection: Suitable protective gloves
- Eye protection: Protective goggles

Material Safety Data Sheet Issue Date: 01-11-02		Product Code: VT-211 Weatherproofing Sealant
--	---	---

9. Physical and chemical properties

- Form: Pastry
- Color: Matt Black
- Odour: Characteristic
- Melting temperature: Not applicable
- Boiling temperature (hPa): Not applicable
- Flash point: >320°C
- Ignition temperature: Not determined
- Vapour pressure (20°C): 15hPa (acetic acid)
- Density (20°C): 1.39
- Solubility in water (20°C): Practically insoluble
- pH Value (g/l water) (°C): Not determined

10. Stability and reactivity

- Hazardous decomposition products: Z-butanone oxime through action of atmospheric humidity
- Hazardous reaction: No dangerous reaction known

11. Toxicological information

- Skin: May cause sensitization * (Methyl tri (enthylmethylketoxime))
- reaction
- Eyes: Possibility irritating
- Further information: * The data are derived from the labeling according to the EC Dangerous Preparation Directive

12. Ecological information

No data available (preparation)

13. Disposal considerations

Can be land-filled for cured product or burned in a chemical incinerator equipped with an afterburner and scrubber. Do not dispose the emptied container unlawfully. Observed all federal, state and local laws.

14. Transport information

No dangerous goods under the transport regulations

Material Safety Data Sheet Issue Date: 01-11-02		Product Code: VT-211 Weatherproofing Sealant
--	---	---

15. Regulatory information

- Labeling (EC): According to the Dangerous Perparation Directive (88/379/EEC) contains:
 - Butan-Z-One O, O', O" – (methylsiylidne) trioxime
 - Hazard symbol: Xi = Irritant
 - R-pharases 43: May causes sensitization by skin contact
 - S-pharases: Z = Keep out of reach of children
 - 24/25 = Avoid contact with skin and eyes
 - 37 = Wear suitable gloves
 - 46 = If swallowed, seek medical advice immediately and show this container or label

16. Other information

The details contained herein are based on our present state of knowledge and experience are characterize our product with regard to any possible safety requirement. We do, however, pass them on without any warranty or property assurances.