

Technical Data Sheet Issue Date: 01-11-02		Product Code: VC-154/155/156 Vital Gasket 1104
--	---	---

Product Description:

Vital Gasket 1104 is a semi-drying grey liquid gasket that uses synthetic rubber as the main ingredients. It is formulated to form a layer thick enough to work efficiently on uneven joint surfaces. It exhibits good resistance to heat, oil, gasoline and particularly LPG. It turns into rubber-like elastic substance upon curing.

Applications:

Applications: Ideal for the purpose of making quality gaskets in garages, workshops, homes and Do-It-Yourself.

Physical Data:

Appearance	Grey high viscosity liquid
Solid Content	46 +/- 1%
Viscosity at 30°C	9000 -12000 cps
Main Solvent	Hydrocarbon Solvent
Main Ingredient	Chloroprene Rubber
Dilution	Toluene
Temperature Range	40°C to 150°C

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water. Puncture the tube with the cap.
2. Apply a thin layer of the adhesive in uniform manner.
3. Assemble after about 1 minute. Application temperature range is between -40°C to +150°C.
4. Replace cap after use and store in cool, dry place.

CAUTION:

Avoid prolonged contact with eyes or skin. In case of eye contact, flush with water for 15 minutes and seek medical attention immediately. In case of skin contact, wipe off and wash with soap and water.

Storage:

Provided the adhesive are stored dry and cool in air tight containers, the storage stability will be at least 12 months from day of delivery ex-works.

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- End -