

<p align="center">Technical Data Sheet Issue Date: 01-11-02</p>		<p align="center">Product Code: VT-120 Contact Adhesive</p>
--	---	--

Product Description:

A premium quality solvent-based synthetic rubber resin adhesive formulated to bond a variety of common materials. It's easy-to-use with longer tack time and offers superior bonding strength.

Applications:

Ideal bonding applications: formica, rubber, cork, leather, fiberglass, polyurethane foam, EVA to wood, metal or concrete. It is also suitable for carpet repair applications.

PHYSICAL DATA:

Appearance	Light brown yellowish high viscosity liquid
Solid Content	22 +/- 1%
Viscosity at 30°C	2900 +/- 100 cps
Main Solvent	Hydrocarbon Solvent
Main Ingredient	Chloroprene Rubber
Dilution	Toluene

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water. Puncture the top of the tube with a sharp tool and install nozzle.
2. Apply the adhesives to both surfaces to give a uniform coating. Allow the solvent to evaporate until the adhesive film is "tacky" (between 3-30 minutes). Apply even pressure to consolidate the bond.
3. Close the cap after use and store in cool, dry place.

CAUTION:

Avoid contact with skin, mouth and eyes. In case of contact with eyes, flush with cold water for 15 minutes. If irritation persists, seek medical attention immediately.

Storage:

Provided the adhesive are stored dry and cool in air tight containers, the storage stability will be at least 12 months from day of delivery ex-works.

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- End -