

<p align="center">Technical Data Sheet Issue Date: 01-11-02</p>		<p align="center">Product Code: VT-133 Vital Nails</p>
--	---	---

Product Description:

A one component, high performance, paste-like construction adhesive sealant formulated to bond a variety of common construction materials. It has strong initial grab, superior adhesion and will not slump on vertical surfaces.

Applications:

Ideal bonding applications: skirting board of wood and PVC, particleboard, masonry, aluminum, galvanized iron, steel, concrete, fibrous cement sheeting, wall brick, concrete and flooring paneling. It is also safe to use on foamed polystyrene and mirror backed tiles.

PHYSICAL DATA:

Appearance	Off white
Specific Gravity	1.35 – 1.4
Consistency	Thixotropic
Open Time	Max. 120 mins at 23°C and 50°C% R.H
Curing Time	24 – 72 hours depending on temperature and porosity of the surface
Water Absorption	Does absorb water to a certain extent which lower the mechanical properties. Not to be used for constructions that will be exposed to severe waterimmersion
Temperature Resistance	-20°C till +80°C (after curing)
Coverage	400 – 1000 gr/m ² . Depending on smoothness and porosity of the surface and desired strength of the construction to be glued

Directions:

1. Surfaces must be clean, dry and free of dirt, grease, oil or water. Puncture the tube with the cap and install nozzle.
2. Squeeze tube and push sealant ahead of nozzle to achieve a smooth finish. Sealant skins in 5 minutes, dries to touch in 1 hour and is fully cured in 24 hours.
3. Uncured sealant can be cleaned up with mineral spirits.
4. Replace cap after use and store in cool, dry place.

CAUTION:

Avoid contact with skin, mouth and eyes. In case of contact with eyes, flush with cold water for 15 minutes. If irritation persists, seek medical attention immediately.

Storage:

In original, unopened packaging at temperature between +5°C and +30°C: 12 months (store and transport, frost free).

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- End -