

<p align="center">Technical Data Sheet Issue Date: 01-07-04</p>		<p align="center">Product Code: VT-311 ABS Pipe Cleaner</p>
--	---	--

Product Description:

VT-311 ABS Pipe Cleaner is specially formulated for the cleaning of ABS pipes in preparation for the assembly using VT-310 ABS Solvent Cement.

Applications:

Besides cleaning the ABS pipes, VT-311 ABS Cleaner can be used to restore brushes and to clean tools soiled with residues of solvent cement. The used ABS Cleaner must not be used again for the cleaning of ABS pipes. VT-311 ABS Cleaner should not be used to dilute the VT-310 ABS Solvent Cement.

SPECIFICATION:

APPEARANCE	Clear Liquid
Odor	Characteristic, non residual
Non volatile matter	0.805 – 0.807
APPLICATION TEMP.	-10°C TO 40°C
SERVICE TEMPERATURE	-10°C TO 60°C
SHELF LIFE	12 MONTHS
Alcohol content	0.15wt%

Directions:

Surfaces must be clean, dry and free of dirt, grease, oil or water.

Clean the surfaces thoroughly using VT-311 ABS Pipe Cleaner. Use fast dry crepe paper or toilet tissue to soak the Cleaner. Always use fresh and clean paper.

Stir adhesive before use.

Apply the adhesive to both surfaces to be bonded with a dry, clean brush to give a uniform coating, with heavier coat at the pipe end.

Allow the solvents to evaporate until the adhesive film is “tacky”. It will take between 3 to 15 minutes depending upon weather condition.

Position the coated surfaces accurately before assemble them. Hold firmly for few seconds to allow initial bonding, then remove surplus adhesive. Joints should not be disturbed for 5 minutes.

12 hours for drying time should be allowed before working pressure, and 24 hours before testing to 1 ½ working pressure.

Safety and first aid directions:

Avoid contact with eyes, skin and mouth.

Use in well ventilated area. In case of contact with eyes, flush with water immediately for 15 minutes. If irritation persists, seek medical attention.

Keep out of reach of children.

Technical Data Sheet Issue Date: 01-07-04		Product Code: VT-311 ABS Pipe Cleaner
--	---	--

Storage

Highly inflammable, keep away from heat source or naked flames. Store in dry and cool place with temperature below +25°C.

Use within 12 months from date of production.

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of various of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.

- End -